

CLAIMS

Claim 1 is canceled.

1 2(currently amended). An arrangement according to claim **11** ~~4~~,
2 where the bracket is attachable to the wall-mounting rod in the vicinities of the
3 end faces.

Claim 3 is canceled.

1 4(currently amended). An arrangement according to claim **11** ~~4~~,
2 wherein the at least one bracket includes a plurality of at least partially
3 identically shaped said brackets.

1 5(currently amended). An arrangement according to claim **11** ~~4~~,
2 where the at least one bracket is configured for attachment to two sections of a
3 wall-mounting rod that are to be coaxially arranged.

1 6(previously presented). An arrangement according to claim 4, where
2 the brackets are configured for attachment to two sections of a wall-mounting
3 rod that are to be coaxially arranged, where the brackets have two attachment
4 sections, said attachment sections of the brackets being engageable with ends
5 of the two sections of the wall-mounting rod at a joint, one of the attachment
6 sections of the brackets being configured for attaching **the** ~~a~~ terminating
7 component for terminating one of the two sections of the wall-mounting rod at
8 an other end of said one of the two sections of the wall mounting rod.

1 7(previously presented). An arrangement according to claim 6, where
2 the attachment section for attaching the terminating component has a device for
3 one of a form-fit and an interference-fit attachment of the terminating
4 component.

1 8(previously presented). An arrangement according to claim 6, where
2 both attachment sections of the bracket have means for guiding the sections of
3 the wall-mounting rod.

1 9(previously presented). An arrangement according to claim 6, where
2 the two attachment sections of the bracket are separated by a land.

Claim 10 is canceled

1 11(previously presented). An arrangement for attaching hygienic articles
2 such that their height will be adjustable, comprising:

3 a wall-mounting rod that has a continuous, guiding profile for guiding a
4 slide, extending over a full length of the wall-mounting rod between ends,
5 at least one bracket for fastening the wall-mounting rod to a surface,
6 wherein the arrangement leaves clear that part of the guiding profile used for
7 guiding the slide,

8 wherein the guiding profile includes a groove, and further comprising a
9 lower terminating component including an extension of the groove, and

10 wherein the bracket is attached to the wall-mounting rod by insertion of
11 an attachment portion of the bracket into an end of the wall-mounting rod.

1 12(currently amended). An arrangement according to claim 11 ~~4~~,
2 where the wall-mounting rod forms a length of stock with a hollow profile and
3 the bracket engages an interior of the hollow profile.

1 13(currently amended). An arrangement according to claim 11 ~~4~~,
2 where accessory items are attachable to the bracket.

1 14(previously presented). An arrangement according to claim 6, wherein
2 the terminating component comprises a terminating collar.

1 15(previously presented). An arrangement according to claim 9, wherein
2 the land forms a joint.

1 16(currently amended). An arrangement according to claim **11** ~~10~~,
2 wherein the groove is on a front surface of the wall-mounting rod.

Claim 17 is canceled.

Claim 18 is canceled.